ACL2VHDL Translator: A Simple Approach to Fill the Semantic Gap

Jun Sawada

IBM Austin Research Laboratory
11501 Burnet Road, MS 904-6H012
Austin, TX 78758
E-mail: sawada@austin.ibm.com

Overview of the Talk

- Language Translation for Hardware Verification
- Our Approach
- Bit Vector Library
- Translation of ACL2 to VHDL
- Application
- Discussion

Two Approaches in Hardware Verification by ACL2

- Proof about abstract models written in the ACL2 language.
  - Pro: Direct. Easy.
  - Cons: Is the model a correct representation of actual HW?
- Proof on hardware written in an HDL, such as Verilog and VHDL.
  - Pro: We get results on actual HW, essential for industry.
  - Cons: Tedious proof about the low-level details of HW.
  - Cons: May require to change the proof when HW changes.
  - Cons: Need a translation from HDL to ACL2. This is not easy.

Two Approaches for Language Translation

- Deep Embedding (e.g DUAL-EVAL)
  - Define an ACL2 interpreter of an HDL.
  - Analyze the evaluation process by the interpreter.
  - Proof can be tedious and confusing because of two-step reasoning.
- Shallow Embedding
  - Use a language translator from an HDL to the ACL2 language.
  - Analyze the result of translation.
  - Translate is more likely to be incorrect: semantic gap.

Typical Problems in Language Translation

- Data types that are not isomorphic.
  - E.g. In ACL2, NIL is both false and an empty list, unlike ML.
    - When translating ACL2 to ML, how to translate NIL?
- Some languages are not well-defined.
  - E.g. C arrays of size bigger than 2^{32}.

Why difficult to translate VHDL?

- Many language features make it difficult to write a complete translator between VHDL and ACL2.
  - Entity and Architecture.
  - Delayed actions.
  - Generics.
  - Sequential and Concurrent Assignment.
    - e.g. Incrementer with input x and output inc in concurrent assignment.

```
carry(32) <= '1';
carry(0 to 31) <= x and carry(1 to 32);
inc(0 to 31) <= din xor carry(1 to 32);
```

How it has been done?

- Typically people write translators from HDL to ACL2 (with some restriction.)
  - Georgelin, Borrione, Ostier 2002
  - Russinoff 1998
- It is laborious to write a complete translator.

Our Approach

- A New Approach
  - Define a translator from ACL2 functions to VHDL functions.
  - Translatable ACL2 functions are defined in terms of a bit vector library.
  - VHDL-level verification tools use the result of translation.
  - Translator does not handle anything like delays, ports, and clocks.
- Why?
  - We only translate a subset of ACL2 language which can be mapped directly to VHDL without loss of semantics.
  - Use ACL2 only for the analysis of algorithms and specifications of HW.
  - Proof on algorithms does not need to change, even if hardware changes.
  - VHDL verification tools are responsible for handling delays, clocks, anything that are related to the actual implementation of hardware.

Overview of the Talk

- Language Translation for Hardware Verification
- Our Approach
- Bit Vector Library
- Translation of ACL2 to VHDL
- Application
- Discussion

IHS : ACL2's Bit Vector Library

- IHS (Integer Hardware Specification) Library by Bishop Brock.
  - A bit is represented by a 0 and 1.
  - A bit vector is represented by an integer.
  - Speedy simulations with many supporting lemmas.
  - Not adequate for the language translation between ACL2 and HDL.
  - 0 and 1 represent both bit and bit vectors.
  - An integer can represent bit vector of many different length.
    - e.g. No way to tell a 32-bit bit vector from a 64-bit bit vector.
  - Hard to define some functions
    - e.g. a function returning the most significant bit of a bit vector.

A new bit vector library: BV Library

- A bit is defined as `(bit 0)` or `(bit 1)`.
- A bit vector is defined as `(BV val size)`.
  - `val` is the integer value of the bit vector and `size` is the length.
- Many basic operations are defined as functions.
- BV library is built on top of IHS.
  - e.g. Bit concatenation function `bv&` is defined in terms of logapp from the IHS library.

```
(defun bv& (a b)
  (declare (xargs :guard (and (bvp a) (bvp b))))
  (bv (logapp (bv-size b) (bv-val b) (bv-val a))
      (+ (bv-size a) (bv-size b))))
```

Some Basic Functions in the BV library.

- `(b-not b)` : Bit negate.
- `(bv-not bv)` : Bit vector negate.
- `(msb bv)` : Returns the most significant bit of bv.
- `(bits bv i j)` : Sub range of a bit vector from i'th bit to j'th.
- `(bv& bv0 bv1)` : Concatenation.
- `(bv+ bv0 bv1)` : Addition.
- `(bv-<< bv sh)` : Shift to left.
- `(bv-gt?  bv0 bv1)` : Greater-than relation.
- `(bv-if b0 bv0 bv1)` : if-then-else.

BV Library Summary

- Quite powerful library to specify functions on bit and bit vectors.
- A floating-point instructions of a PowerPC™ media unit has been specified.
- Many lemmas from the IHS library are or can be imported to the BV library.
  - However, need more work to expand it.

ACL2VHDL Translator

- Translates ACL2 function defined in terms of the functions from the BV library, `let` and `let*`.
  - No `if`-statement. Use `bv-if` or `b-if`.
  - No recursive functions.
- Conversion Process:
  - Parsing.
  - Type Inference.
  - VHDL code generation.

Conversion Tricks

- We need to implement a type inference system, because ACL2 language is dynamically typed, but VHDL is statically typed.
- Code generation is simple mapping as all BV library functions are re-defined in VHDL.
- Name conflicts in the let expressions are resolved by renaming.
- Addition of 32-bit integer types in ACL2, since VHDL integers are 32-bit integers.

Carry Generation in ACL2

```
(defun lc8 (v8)
  (declare (xargs :guard (and (bvp v8)
                              (equal (bv-size v8) 8))))
  (b&& (bv-and-all (bits v8 1 7))
       (bv-and-all (bits v8 2 7))
       (bv-and-all (bits v8 3 7))
       (bv-and-all (bits v8 4 7))
       (bv-and-all (bits v8 5 7))
       (bv-and-all (bits v8 6 7))
       (bitn 7 v8)
       *b1*))
```

Translated Carry Function

```
function lc8(v8 : std_ulogic_vector)
  return std_ulogic_vector is
  variable result : std_ulogic_vector(0 to 7);
begin
   result := (and_reduce(bits(v8,1,7)) &
              (and_reduce(bits(v8,2,7)) &
               (and_reduce(bits(v8,3,7)) &
                (and_reduce(bits(v8,4,7)) &
                 (and_reduce(bits(v8,5,7)) &
                  (and_reduce(bits(v8,6,7)) &
                   (bitn(7,v8) &
                    b2bv(b1))))))));
   return result;
end lc8;
```

Carry look ahead signal in ACL2

```
(defun gc8 (v32)
  (declare (xargs :guard (and (bvp v32)
                              (equal (bv-size v32) 32))))
  (b&& (bv-and-all (bits v32 8 31))
       (bv-and-all (bits v32 16 31))
       (bv-and-all (bits v32 24 31))))
```

Carry look ahead signal in VHDL

```
function gc8(v32 : std_ulogic_vector)
   return std_ulogic_vector is
   variable result : std_ulogic_vector(0 to 2);
begin
   result := (and_reduce(bits(v32,8,31)) &
              (and_reduce(bits(v32,16,31)) &
               b2bv(and_reduce(bits(v32,24,31)))));
   return result;
end gc8;
```

Carry and Increment

```
(defun carry32 (v32)
  (declare (xargs :guard (and (bvp v32)
                              (equal (bv-size v32) 32))))
  (let ((lc_0_7 (lc8 (bits v32 0 7)))
        (lc_8_15 (lc8 (bits v32 8 15)))
        (lc_16_23 (lc8 (bits v32 16 23)))
        (lc_24_31 (lc8 (bits v32 24 31)))
        (gc (gc8 v32)))
    (bv&& (bv-if (bitn 0 gc) lc_0_7 (bv 0 8))
          (bv-if (bitn 1 gc) lc_8_15 (bv 0 8))
          (bv-if (bitn 2 gc) lc_16_23 (bv 0 8))
          lc_24_31)))

(defun inc2 (v32)
  (declare (xargs :guard (and (bvp v32)
                              (equal (bv-size v32) 32))))
  (bv-xor v32 (carry32 v32)))
```

Carry and Increment in VHDL

```
function carry32(v32 : std_ulogic_vector)
 return std_ulogic_vector is
 variable lc_0_7 : std_ulogic_vector(0 to 7);
 variable lc_8_15 : std_ulogic_vector(0 to 7);
 variable lc_16_23 : std_ulogic_vector(0 to 7);
 variable lc_24_31 : std_ulogic_vector(0 to 7);
 variable gc : std_ulogic_vector(0 to 2);
 variable result : std_ulogic_vector(0 to 31);
begin
 lc_0_7 := lc8(bits(v32,0,7));
 lc_8_15 := lc8(bits(v32,8,15));
 lc_16_23 := lc8(bits(v32,16,23));
 lc_24_31 := lc8(bits(v32,24,31));
 gc := gc8(v32);
```

Carry and Increment in VHDL : Continued

```
 result := (ite(bitn(0,gc),lc_0_7,bv(X"0",8)) &
            (ite(bitn(1,gc),lc_8_15,bv(X"0",8)) &
             (ite(bitn(2,gc),lc_16_23,bv(X"0",8)) &
              lc_24_31)));
 return result;
end carry32;

function inc2(v32 : std_ulogic_vector)
 return std_ulogic_vector is
 variable result : std_ulogic_vector(0 to 31);
begin
 result := (v32 xor carry32(v32));
 return result;
end inc2;
```

A Simple Incrementer

- In ACL2

```
(defun inc (v0)
  (declare (xargs :guard (and (bvp v0)
                              (equal (bv-size v0) 32))))
  (bv+ v0 (bv 1 32)))
```

- In VHDL translation:

```
function inc(v0 : std_ulogic_vector)
    return std_ulogic_vector is
    variable result : std_ulogic_vector(0 to 31);
begin
    result := (v0 + bv(X"1",32));
    return result;
end inc;
```

Application

- Floating-Point instruction verification.
- Multiplier Verification

Verification of Floating-Point Instruction

- We wrote a specification of floating-point instructions for a media unit.
- ACL2VHDL was used to the spec to VHDL.
- Run a SAT procedure to verify precision conversion instructions implemented in hardware.



Multiplier Verification

- Sandip Ray worked on the integration of ACL2 and SixthSense, an IBM internal tool for VHDL verification.
- Working on a multiplier built in terms of Booth encoder and Carry Save Adders.
- We proved the correctness of multiplier algorithm in ACL2, provided that the hardware satisfies a number of proof obligations.
- The proof obligations are translated, checked by SixthSense and then imported back into ACL2 as a theorem.
- This is an on-going work.

Multiplier Verification Flow



Discussion

- Bare-bone translator against full-fledged translators.
  - ACL2VHDL is a simple translator, but flexible for wide applications.
  - No knowledge about time, unit, port, etc.
- Recursive functions are useful or not?
  - VHDL has a limited form of recursive functions.
  - `if`-statement needs to be added to the conversion.
  - Currently, recursive functions can be used in verification with extra steps.
    - First verify theorems using recursive functions.
    - Define and prove there is an non-recursive function equivalent to it.
    - Use the non-recursive version functions for HW verification.