Verification of an In-place Quicksort in ACL2

ACL2 Workshop

Grenoble, France

April 9, 2002

Sandip Ray

sandip@cs.utexas.edu

Rob Sumners

robert.sumners@amd.com

⌊ Brief Introduction ⌋

- Goal: to demonstrate techniques for proving properties of stobj-based functions

- We chose in-place Quicksort as a common, well-understood example

  – The in-place Quicksort may also be of practical use in writing ACL2 programs which need to efficiently sort a large list of objects

- Supporting materials for this paper include the necessary definitions and proofs

⌊ In-place Quicksort ⌋

- Sort an array in-place by recursively dividing the problem and subsequently merging the results from this division

  – Choose a *splitter* object from the array and partition the input array into two *halves* and recursively sort the two *halves*

  – No subsequent merging is necessary since all elements in the *upper half* will be greater than the elements in the *lower half*

- We would like our definition of Quicksort to map an unsorted list to a sorted list (as opposed to using arrays)

  – So, in order to have the efficiency of array access and update, we will need to use a (local) single-threaded object

⌊ Single-Threaded Objects (stobjs) ⌋

- Stobjs were introduced in ACL2 2.4

  – Stobjs consist of a fixed set of fields, some of which may be arrays

  – The use of stobjs is syntactically restricted to ensure that the applicative semantics coincides with the destructive implementation

- In ACL2 2.6, several enhancements were made to stobjs:

  – Stobjs are more efficient, arrays can be resized, and stobjs may now be local to a given function

  – Stobj arrays in ACL2 are *comparable* in efficiency to arrays in C

    ◦ stobj array access and update (essentially) add the overhead of a function call

⌊ Definition of In-Place Quicksort-1 ⌋

- Definition of main **`qsort`** wrapper function:

```
(defun qsort (x)
  (with-local-stobj qstor
      (mv-let (rslt qstor)
          (let* ((size (length x))
                 (qstor (alloc-qs size qstor))
                 (qstor (load-qs x 0 size qstor))
                 (qstor (sort-qs 0 (1- size) qstor)))
            (mv (extract-qs 0 (1- size) qstor)
                qstor))
        rslt)))
```

- Definition of recursive sorting function **`sort-qs`**:

```
(defun sort-qs (lo hi qstor)
  (declare (xargs :stobjs qstor))
  (if (ndx<= hi lo)
      qstor
    (mv-let (index qstor)
        (split-qs lo hi (objsi lo qstor) qstor)
      (if (ndx<= index lo)
          (sort-qs (1+ lo) hi qstor)
        (let ((qstor (sort-qs index hi qstor)))
          (sort-qs lo (1- index) qstor))))))
```

⌊ Definition of In-Place Quicksort-2 ⌋

- Definition of array splitting function **split-qs**:

```
(defun split-qs (lo hi splitter qstor)
  (declare (xargs :stobjs qstor))
  (if (ndx< hi lo)
      (mv lo qstor)
    (let* ((swap-lo (<<= splitter (objsi lo qstor)))
           (swap-hi (<< (objsi hi qstor) splitter))
           (qstor (if (and swap-lo swap-hi)
                      (swap lo hi qstor)
                    qstor)))
      (split-qs (if (implies swap-lo swap-hi)
                    (1+ lo)
                  lo)
                (if (implies swap-hi swap-lo)
                    (1- hi)
                  hi)
                splitter qstor))))
```

- Definition of the stobj **qstor**:

```
(defstobj qstor
  (objs :type (array T (0))
        :resizable t
        :initially nil))
```

⌊ Specification and Decomposition ⌋

- The output of `qsort` is an ordered permutation of the input
  - We use the ACL2 total order `<<`
- We prefer to first define a simple insertion sort `isort` and:
  - Prove that this function returns an ordered permutation (standard ACL2 exercise)
  - Prove `(thm (equal (qsort x) (isort x)))`
    - In the paper we add a `(true-listp x)` hypothesis, but this is only a matter of convenience
- `isort` can be viewed as an *intermediate* function which separates the specification from the implementation
  - We will introduce additional intermediate functions to aid in the proof

⌊ Reasoning about stobj functions ⌋

- Proofs about stobj functions encounter some common problems

  – Stobjs are frequently parameters (and return values) of every component function

  – Various properties will need to be proven to commute over the operations which update the stobj

    ◦ For example (with $[\mathtt{a}, \mathtt{b}] \cap [\mathtt{x}, \mathtt{y}] = \emptyset$):

```
(equal (extract-qs a b (sort-qs x y qs))
       (extract-qs a b qs))
```

  – Various invariants may need to be defined and proven to hold of the functions which update the stobj

  – The "logic" definition of the function will often be unwieldy to work with directly

    ◦ Intermediate functions are often needed to factor the complexity of the proof into more manageable pieces

⌊ Intermediate Function #1 ⌋

• Our first intermediate function is an applicative Quicksort function:

```
(defun qsort-split (lst)
  (mv (lower-part lst (first lst))
      (upper-part lst (first lst))))

(defun qsort-fn (lst)
  (if (endp lst) nil
    (if (endp (rest lst))
        (list (first lst))
      (mv-let (lower upper)
          (qsort-split lst)
        (if (endp lower)
            (cons (first upper)
                  (qsort-fn (rest upper)))
          (append (qsort-fn lower)
                  (qsort-fn upper)))))))
```

⌊ Intermediate Function #1, continued ⌋

• The definitions of `lower-part` and `upper-part` model `split-qs`

```
(defun lower-part (x s)
  (cond
   ((endp x) nil)
   ((and (<<= s (first x))
         (<< (last-val x) s))
    (cons (last-val x)
          (lower-part (del-last (rest x)) s)))
   ((and (<<= s (first x))
         (<<= s (last-val x)))
    (lower-part (del-last x) s))
   ((and (<< (first x) s)
         (<< (last-val x) s))
    (cons (first x)
          (lower-part (rest x) s)))
   (t
    (cons (first x)
          (lower-part (del-last (rest x)) s)))))
```

• Relevant properties of `upper-part` and `lower-part`...

⌊ Refining the `split` function ⌋

• The definition of **`qsort-split`** is difficult to correlate directly with **`split-qs`**, so we introduce another refinement:

```
(defun in-situ-qsort-split (lst)
  (let* ((merge (merge-func lst (first lst)))
         (ndx (walk lst (first lst)))
    (mv (first-n ndx merge)
        (last-n ndx merge))))
```

• We then define **`in-situ-qsort-fn`** to be **`qsort-fn`** with **`in-situ-qsort-split`** replacing **`qsort-split`**

– The equivalence of **`in-situ-qsort-fn`** with **`qsort-fn`** easily reduces to proving the equivalence of **`in-situ-qsort-split`** with **`qsort-split`**

⌊ Relevant properties... ⌋

- Properties relating **in-situ-qsort-split** with **split-qs**:

```
(defthm walk-split-qs-equal
  (implies (and (natp lo) (natp hi))
   (equal (mv-nth 0 (split-qs lo hi x qs))
          (+ lo (walk (extract-qs lo hi qs) x)))))

(defthm merge-func-split-qs-equal
  (implies (and (natp lo) (natp hi))
   (equal (extract-qs lo hi
            (mv-nth 1 (split-qs lo hi x qs)))
          (merge-func (extract-qs lo hi qs) x))))
```

- Relating **sort-qs** with **in-situ-qsort-fn**:

```
(defthm sort-qs-equal-in-situ-qsort-fn
  (implies (and (natp lo) (natp hi) (<= lo hi))
   (equal (extract-qs lo hi (sort-qs lo hi qs))
          (in-situ-qsort-fn (extract-qs lo hi qs)))))
```

⌊ Concluding Remarks ⌋

- Previous work in Coq proved Quicksort using Hoare-style proof
  - i.e. loop invariants, preconditions, postconditions
  - Their proof is shorter, but comparison is difficult due to incongruences in libraries and definitions
- Quicksort is not the best example of the use of intermediate functions
  - This approach is more effective when stobjs are used to optimize the evaluation of applicative functions (e.g. hash tables, memoization, etc.)
- Future work:
  - Multi-threaded Quicksort with shared `qstor`
    - Proof requirements ensure that applicative semantics are still consistent with implementation
  - Develop library to aid in reasoning about stobjs